



**RAKAM**

# TECHNICAL DATA SHEET

## 506 RAK COAT CANVAS (30/6)

(Thermal Insulation Canvas Coating)



**RAK COAT-CANVAS** is a tough, flexible adhesive and an antifungal sealant forming a durable seal against air leakage. Due to its excellent water, U. V and abrasion resistance it can be used in outdoor as well as indoors in insulation system on metal duct.

ADVANTAGES	SURFACE PREPARATION	ORDERING GUIDE																															
<ul style="list-style-type: none"> <li>• Good adhesion</li> <li>• Water resistant</li> <li>• Non toxic &amp; non flammable</li> <li>• Ultra violet resistance</li> <li>• Antifungal &amp; antibacterial</li> <li>• Suitable for Middle East climatic conditions</li> </ul>	<p>The surface should be clean, dry and free from oil, grease and loose particles.</p>	<p>PRODUCT NO. 506</p> <p>STANDARDS ASTM C - D2240 BS EN 12390 Pt 8 2000</p>																															
	<p><b>APPLICATION</b></p> <p>Dilute RAK Coat-Canvas with 18% to 25 % soft water and apply as a primer coat @ 2 to 3m<sup>2</sup> per liter. After applying primer coat immediately imbed the selected fabric tagging fabric smoothly in to the wet primer coating. Apply two finish coat of undiluted RAK Coat-Canvas at the rate of 2.5 to 3m<sup>2</sup> liter. It is very important to ensure that each coat of RAK Coat-Canvas is totally cured before next coat is applied. To avoid pin hole in coating system, use short haired roller.</p>	<p>PACKAGING 20 kg / 5 Kg Packs</p> <p>COLOR White</p>																															
TYPICAL PROPERTIES	HEALTH AND SAFETY																																
<table border="0"> <tr> <td>Binder</td> <td>Special synthetic resin polymer</td> </tr> <tr> <td>Color</td> <td>White</td> </tr> <tr> <td>Consistency</td> <td>Thixotropic like paste</td> </tr> <tr> <td>Solid Content</td> <td>70%</td> </tr> <tr> <td>Viscosity</td> <td>100,000 cps brookfield spindle 6 rpm @ 30°C</td> </tr> <tr> <td>Specific Gravity</td> <td>1.3</td> </tr> <tr> <td>Bonding Time</td> <td>45 minutes (at20°C)</td> </tr> <tr> <td>Service Temp</td> <td>5-100°C</td> </tr> <tr> <td>Flash Point</td> <td>Non Flammable</td> </tr> <tr> <td>Shelf Life</td> <td>Not below 5°C, protect from high temp, shelf life is 12 months from date of manufacture in unopened containers</td> </tr> <tr> <td>Coverage</td> <td>Approx 3.2m<sup>2</sup> per liter</td> </tr> <tr> <td>Harness Shore A</td> <td>61 (ASTMD 2240)</td> </tr> <tr> <td>UV Resistance, hrs</td> <td>10,000. No deterioration or color fade</td> </tr> <tr> <td>Drying Time</td> <td>22°C RH 50% (5 hours)</td> </tr> <tr> <td>Water Vapor tran Water permeability @ 3 bar pressure</td> <td>1.525</td> </tr> <tr> <td>BS EN 12390 Part 8:2000</td> <td>NIL</td> </tr> </table>	Binder	Special synthetic resin polymer	Color	White	Consistency	Thixotropic like paste	Solid Content	70%	Viscosity	100,000 cps brookfield spindle 6 rpm @ 30°C	Specific Gravity	1.3	Bonding Time	45 minutes (at20°C)	Service Temp	5-100°C	Flash Point	Non Flammable	Shelf Life	Not below 5°C, protect from high temp, shelf life is 12 months from date of manufacture in unopened containers	Coverage	Approx 3.2m <sup>2</sup> per liter	Harness Shore A	61 (ASTMD 2240)	UV Resistance, hrs	10,000. No deterioration or color fade	Drying Time	22°C RH 50% (5 hours)	Water Vapor tran Water permeability @ 3 bar pressure	1.525	BS EN 12390 Part 8:2000	NIL	<p>As with all chemical products, caution should always be exercised. Protective clothing, such as gloves and goggles, should be worn (see packaging for specific instructions). Treat any splashes to the skin or eyes with fresh water immediately. Should any of the product be accidentally swallowed, do not induce vomiting but call for medical assistance immediately. Ensure the container is available for the medical attendant to examine any relevant instructions and contents details. Reseal all containers after use and ensure product is stored as instructed on the safety section of the labelling.</p>
Binder	Special synthetic resin polymer																																
Color	White																																
Consistency	Thixotropic like paste																																
Solid Content	70%																																
Viscosity	100,000 cps brookfield spindle 6 rpm @ 30°C																																
Specific Gravity	1.3																																
Bonding Time	45 minutes (at20°C)																																
Service Temp	5-100°C																																
Flash Point	Non Flammable																																
Shelf Life	Not below 5°C, protect from high temp, shelf life is 12 months from date of manufacture in unopened containers																																
Coverage	Approx 3.2m <sup>2</sup> per liter																																
Harness Shore A	61 (ASTMD 2240)																																
UV Resistance, hrs	10,000. No deterioration or color fade																																
Drying Time	22°C RH 50% (5 hours)																																
Water Vapor tran Water permeability @ 3 bar pressure	1.525																																
BS EN 12390 Part 8:2000	NIL																																
	RECOMMENDED TOOLS																																
	Brush, shorthaired roller and airless spray.																																
	STORAGE																																
	Store away from direct sunlight. Keep in dry place preferably 20 to 30°C																																

